

Floorstanding cistern Universal for floorstanding WC pan
82866.0



TECHNICAL DATA

Order no.	82866.0
Certified to	EN 14055
matching for	Floorstanding WC pan, order no. 82333.1 Floorstanding WC rimless, order no. 82333.6
Specification	floorstanding Flushing mechanism Dual-Flush water condensation insulation Charge 730 – 6/3-l (4,5/3-l-flush)
Water inlet	side left, side right 3/8"
Weight	21,5 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 220 - 305 mm only LAUFEN-connection, order no. 89902.5 Water inlet hose
Colours	see colour table

SPECIFICATION TEXT

Floorstanding cistern Universal KARTELL BY LAUFEN, sanitary ceramic EN 14055, dimensions 400/410 x 140 x 980 mm
Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
side left, side right (3/8")
matching floorstanding WC pan, order no. 82333.1 and floorstanding WC rimless, order no. 82333.6
Special feature: water condensation insulation
Further options: Surface refinement LCC (only white)
Order no. 82866.0

TECHNICAL DRAWINGS / S 1 : 20

