

SPECIAL ARTICLES
Floorstanding Cistern
UNIVERSAL
82866.1



TECHNICAL DATA

Order no.	82866.1	Mounting acc. incl.	Fastening kit
Certified to	EN 14055		Angle valve for rear water inlet
matching for	Floorstanding WC pan Lb3, order no. 82168.4 Laufen Pro, order no. 82295.2, 82295.6 Kartell by Laufen, order no. 82333.1, 82333.6 Palace, order no. 82370.1 Palomba Collection, order no. 82380.6		Water inlet hose
Specification	floorstanding Flushing mechanism Dual-Flush water condensation insulation Charge 881 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)	Colours	see colour table
Water inlet	concealed top left rear, 1/2" brass	SPECIFICATION TEXT Floorstanding cistern UNIVERSAL, sanitary ceramic EN 14055 dimensions 400/410 x 140 x 980 mm Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush) concealed water inlet top left rear, 1/2" brass matching floorstanding WC pan, Lb3 order no. 82168.4, Laufen Pro order no. 82295.2, 82295.6, Kartell by Laufen order no. 82333.1, 82333.6, Palace order no. 82370.1, Palomba Collection order no. 82380.6 Special feature: water condensation insulation Order no. 82866.1	
Weight	21,5 kg		

TECHNICAL DRAWINGS / S 1 : 20

