



**TECHNICAL DATA**

Order no.	82933.2
Certified to	EN 14055
matching for	Floorstanding WC pan order no. 82433.1 / Charge 000,, 82433.7 / Charge 000
Specification	Flushing mechanism Dual-Flush With water condensation insulation: Charge 872 – 5/3-l (6/3-l-flush, 4,5/3-l-flush) Without water condensation insulation: Charge 876 – 5/3-l (6/3-l-flush, 4,5/3-l-flush)
Water inlet	side left, side right, 3/8" brass
Weight	13,0 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	Angle valve for water inlet Water inlet hose
Colours	see colour table

**SPECIFICATION TEXT**

Cistern KARTELL BY LAUFEN, sanitary ceramic  
EN 14055  
dimensions 380 x 160 x 395 mm  
Dual-Flush 5/3-l (6/3-l-flush, 4,5/3-l-flush)  
water inlet side left, side right, 3/8" brass  
matching floorstanding WC pan rimless, order no. 82433.1/option 000,  
82433.7/option 000  
Special feature: with or without water condensation insulation  
Further options: Surface refinement LCC (only white)  
Order no. 82933.2

**TECHNICAL DRAWINGS / S 1 : 20**

