

**Floorstanding cistern Universal for floorstanding WC pan
82866.3**



TECHNICAL DATA

Order no.	82866.3
Certified to	EN 14055
matching for	Floorstanding WC pan rimless, order no. 82333.6
Specification	floorstanding Flushing mechanism Dual-Flush water condensation insulation Charge 883 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	bottom left, 1/2" plastic
Weight	21,5 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 220 - 305 mm only LAUFEN-connection, order no. 89902.5 Angle valve for water inlet Water inlet hose
Colours	see colour table

SPECIFICATION TEXT

Floorstanding cistern Universal KARTELL BY LAUFEN, sanitary ceramic EN 14055
 dimensions 400/410 x 140 x 980 mm
 Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
 water inlet bottom left, 1/2" plastic
 matching floorstanding WC pan rimless, order no. 82333.6
 Special feature: water condensation insulation
 Order no. 82866.3

TECHNICAL DRAWINGS / S 1 : 20

