



**TECHNICAL DATA**

Order no.	82695.0
Certified to	EN 14055
matching for	Floorstanding WC pan order no. 82495.5 / Charge 000/204 82495.6, 82495.7, 82495.8 / Charge 000/204, 82495.9
Specification	Flushing mechanism Geberit, Dual-Flush With water condensation insulation: Charge 278 – 6/3-l-flush Charge 750 – 4,5/3-l-flush (Green Version)
Water inlet	side left, side right (3/8"), rear (3/8"-1/2")
Weight	12,2 kg
Mounting acc. incl.	Corner valve for rear water inlet
Colours	see colour table

**SPECIFICATION TEXT**

Cistern LAUFEN PRO, sanitary ceramic  
EN 14055, dimensions 380 x 175 x 360 mm  
Dual-Flush 6/3-l option 278  
Dual-Flush 4,5/3-l option 750 (Green Version)  
water inlet side left, side right (3/8"), rear (3/8"-1/2")  
matching floorstanding WC pan, order no. 82495.5/option 000/204,  
82495.6, 82495.7, 82495.8/option 000/204, 82495.9  
Special feature: water condensation insulation  
Further options: Surface refinement LCC (only white)  
Order no. 82695.0

**TECHNICAL DRAWINGS / S 1 : 20**

