

SPECIAL ARTICLES
Floorstanding Cistern
UNIVERSAL
82866.0



TECHNICAL DATA

Order no.	82866.0
Certified to	EN 14055
matching for	Floorstanding WC pan Lb3, order no. 82168.4 Laufen Pro, order no. 82295.2, 82295.6 Kartell by Laufen, order no. 82333.1, 82333.6 Palace, order no. 82370.1 Palomba Collection, order no. 82380.6
Specification	floorstanding Flushing mechanism Dual-Flush water condensation insulation Charge 882 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	side left, side right, 3/8" brass
Weight	21,5 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	Angle valve for water inlet Water inlet hose
Colours	see colour table

SPECIFICATION TEXT

Floorstanding cistern UNIVERSAL, sanitary ceramic
EN 14055
dimensions 400/410 x 140 x 980 mm
Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
water inlet side left, side right, 3/8" brass
matching floorstanding WC pan, Lb3 order no. 82168.4,
Laufen Pro order no. 82295.2, 82295.6,
Kartell by Laufen order no. 82333.1, 82333.6, Palace order no. 82370.1,
Palomba Collection order no. 82380.6
Special feature: water condensation insulation
Order no. 82866.0

TECHNICAL DRAWINGS / S 1 : 20

