

## **UN 38.3 Test Summary Report**

Lithium Cell or Battery Test Summary in Accordance with Section 2.9.4 UN Model Regulations and Sub-section 38.3 of the UN Manual of Tests and Criteria, Part III, subsection 38.3.5

[a] ⊠ Cell □ Battery □ Product ⊠ Tested Type Part #: SL-760	[d] Unique report ID: 15Q-605	***************************************
☐ Same Type Part #:	[e] Report date: 2003.04.01	***************************************
[b] Manufacturer Tadiran Batteries GmbH Industriestrasse 22 63654 Buedingen Germany T. +49 6042 954 0 info@tadiranbatteries.de www.tadiranbatteries.de	[c] Test Laboratory Tadiran Batteries Ltd. P.O. Box 1 Kiryat Ekron Israel 70500 T. +972 8 9 44 560 sales@tadiran-batt.com www.tadiran.com	

☑ Same Type Part Numbers # (all): Standard: 11 1 07601 00, Tags: 11 1 07602 00, Pins: 11 1 07603 00, Pins radial: 11 1 07606 00, Polarised tags: 11 1 07608 00, all other configurations with harness and cable of this cell with part number: 11 1 0760x xx or 14 1 0760x xx.

[f] (i) □ Li-ion ⊠ Li-metal.	
(iv) <u>Description:</u> Primary (non-rechargeable) 3.7 V Lithium Thionyl Chloride (Li-SOCI2) battery, as 1 (one) "AA" sized SL-760 cell. The SL-760 cell may come with optional suffixes consisting of a "/" one or more letters and a digit. These suffixes indicate different types of finishing to the cell (for ex Standard, T-Tab, P-Pin, etc.).  Tadiran manufactures all cells/batteries under a quality management system as required under this	followed by cample, S-
(ii) Mass: 20 g	
(iii) ☐ Watt hour rating or ☑ Lithium content: 0.65 g	
(v) ⊠ Cell □ Battery □ Product. Model number/Part number: SL-760	

[g] List of Tests Conducted	Result (Pass / Fa	il / N.A.)	Test record reference
38.3.4.1 T.1: Altitude simulation	Pass		Page 5
38.3.4.2 T.2: Thermal test	Pass		Page 6
38.3.4.3 T.3: Vibration	Pass		Page 7
38.3.4.4 T.4: Shock	Pass		Page 8
38.3.4.5 T.5: External short circuit	Pass		Page 9
38.3.4.6 T.6: Impact/Crush (cell only test)	Pass		Page 10
38.3.4.7 T.7: Overcharge (N.A for Li-metal only)	N.A.		N.A.
38.3.4.8 T.8: Forced discharge (cell only test)	Pass		Page 11
[h] Battery assembly: ⊠ Not Applicable. □ UN38.	3.3 (f) UN38.3.3 (g)		
[i] Test Reference: UN Manual of Tests and Criteria	a, Part III, sub-section 3	8.3. <i>third r</i>	evised edition, am. 1
[j] Signatory A. Date: 2018.02.12  Name: Marc Henn  Title: Application Engineering Manager		[j] Signatory B. Date: 2018.02.12  Name: Olaf G. Lichtlein  Title: General Manager	
Signature.		Signature.	1////

Important! The above signatory / signatories affirm that this document is a true and correct summary of the original individual tests and test data. The original test data is confidential information available to competent State Authorities with valid identification and only upon their formal request. Disclosure of the original test data to any other entity upon its request will be considered by Tadiran and, should Tadiran consider this request is with merit, may be subject to the prior execution of a nondisclosure agreement.

Wast 1