

URINALS

Siphonic urinal CAPRINO PLUS

84206.5



TECHNICAL DATA

| | |
|---------------------|---|
| Order no. | 84206.5 |
| Certified to | EN 80, EN 13407, EN 15091 |
| matching for | LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5 |
| Specification | 1-l flushing electronic controlled siphonic urinal Electronic control 230 V Only in combination with fixing set, order no. 89280.8 |
| Water inlet | concealed, 1/2" |
| Outlet | horizontal or vertical |
| Flushing | 1 l |
| Flushing rate | minimum 0.3 l/s |
| Weight | 20,0 kg |
| Mounting acc. incl. | Electronic control system 230 V with all mounting accessories Charge 000 – without fly, 1-litre siphon with horizontal and vertical outlet DN 40 (standard CH) Charge 400 – with fly, 1-litre siphon with horizontal and vertical outlet DN 40 (standard CH) Charge 401 – without fly, 1-litre siphon with horizontal and vertical outlet DN 50 (standard Europe, except CH and UK) Charge 411 – with fly, 1-litre siphon with horizontal and vertical outlet DN 50 (standard Europe, except CH and UK) |

| | |
|---------------------|---|
| Mounting acc. incl. | Charge 407 – without fly, 2-litre siphon with horizontal outlet DN 40 (standard UK) Charge 417 – with fly, 2-litre siphon with horizontal outlet DN 40 (standard UK) Wall fixing set M8 LAUFEN, order no. 89280.8 |
|---------------------|---|

| | |
|---------------------|---|
| Mounting acc. excl. | Stone screw fixing set M8 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4 |
|---------------------|---|

Colours see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-CAPRINO PLUS, sanitary ceramic, electronic control
EN 80, EN 13407, EN 15091, dimensions 320 x 350 x 645 mm
1-l flush, water inlet concealed 1/2", outlet horizontal or vertical, flushing rate minimum 0.3 l/s
electronic control system 230 V with all mounting accessories, 1-litre siphon with horizontal and vertical outlet DN 50 (standard Europe, except CH and UK) and outlet DN 40 (standard CH), 2-litre siphon with horizontal outlet DN 40 (standard UK)
Special feature: Vacuum and performance tested
Further options: Surface refinement LCC (only white), with fly, LIS CU3 concealed frame for urinal with integrated control
Order no. 84206.5

TECHNICAL DRAWINGS / S 1 : 20

